



# Standard Driveway Crack Filler

## Asphalt Emulsion Based Crack Filler

- Fills & Seals Cracks in Asphalt Driveways
- Seals Out Moisture
- Easy to Apply
- Dries Black



### Manufacturer:

JETCOAT  
472 Brehl Avenue  
Columbus, Ohio  
Phone: 800-394-0047  
Fax: 614-279-7201  
www.JETCOATinc.com

### Description

An asphalt emulsion crack filler designed for sealing cracks up to 1/2" wide in asphalt pavement surfaces.

### Uses

- All types of asphalt pavements.
- DO NOT USE on concrete or masonry surfaces.
- Do not apply to cracks/holes containing water.

### Surface Preparation

For best results, clean all cracks free of dust, dirt, and debris by broom, water spray or power blower. Assure all cracks are free of water, vegetation and existing crack filler. Cracks deeper than 1" should be filled with backer-rod or a suitable material to 1/2" depth.

### Application

JETCOAT Standard Driveway Crack Filler is packaged ready to use. Cut tip of spout to desired width and puncture seal. Apply material into crack with caulking gun.

### Drying Time

Allow Crack Filler to cure for 24-48 hours prior to sealing or opening to traffic.

### Clean Up

- While wet, use soap and water.
- When Dry, kerosene or mineral spirits.

### Weather Conditions

- Apply when temperatures are expected to be above 50 °F for at least 48 hours. Do not apply when rain is imminent within 48 hours.

### Coverage (Approximate)

- One 10 ounce tube will fill approximately 6-12 feet of cracks. Ultimate coverage will be dependent upon depth and width of cracks.

### Precautions

- Do Not Thin
- Do Not Store Container At Temperatures Below 40° F
- Do Not Freeze
- Do Not Allow Traffic Until Fully Cured

### Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 10 Gm/Liter Max
- KEEP OUT OF REACH OF CHILDREN

This product does not contain any California Proposition 65 Chemicals.

**Standard Driveway Crack Filler**  
Asphalt Emulsion Based Crack Filler

Form No.: JC-TD23739

## Packaging

Item #	Container Size	Pack	Weight
23739	10 Oz. Tube	12	10.1 lbs.

\* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Asphalt	8052-42-4
Clay	1332-58-7
Polymer Latex	Proprietary
Water	7732-18-5