



Premium All-Weather Roof Patch & Flashing Cement

Professional Quality Water Repellent Sealing Compound

- Stops Roof Leaks Instantly
- Long-Lasting Protection
- Fiber Reinforced
- Easy-To Use-Trowel Grade Formula
- Commercial & Residential Use
- Meets or Exceeds all Requirements of ASTM D 4586 ,TYPE I & 100% Wet Surface Adhesion per ASTM D-3409



Manufacturer:

JETCOAT
 472 Brehl Avenue
 Columbus, Ohio
 Phone: 800-394-0047
 Fax: 614-279-7201
 www.JETCOATinc.com

Description

This multi-purpose patch material features a special blend of refined asphalts and adhesion promoters designed to bond rapidly to moist, damp, wet or dry surfaces. It provides water repellency when conventional cements just won't stick. Can also be used on flashings, vents, skylights, metal joints, seams, coping and chimneys.

Uses

- Splits & Seams
- Vents
- Metal Joints
- Coping
- Flashings
- Skylights
- Chimneys

Surface Preparation

For best results, clean surface with brush or broom, removing all loose sediment and dirt. Nail down any loose parts.

Application

Pails: Using a trowel, spread All-Weather Roof Patch & Flashing Cement onto the surface at a thickness of about 1/8"; making sure to smooth down the edges. Mend cracks, splits or blisters by troweling the cement to the affected area and three inches beyond. Embed Resin Treated Multi-Purpose Reinforcing Fabric into the repaired area and topcoat with another layer of roof patch material.

Tubes: Trim Nozzle to desired bead size. Puncture foil at innerbase of nozzle. Using a caulking gun,

apply to a minimum wet thickness of 1/4". Allow at least 24 hours to dry (70°F and less than 50% humidity with no rain) before applying a surface coating.

Drying Time

Dries to the touch in 8-24 hours, depending on weather conditions.

Clean Up

- Clean up with waterless hand cleaner immediately after use.

Weather Conditions

- Can be used in wet or dry conditions.

Coverage (Approximate)

- Approximately 12 square feet per gallon.
- One 10 ounce tube will fill approximately 30 lineal feet at 1/4" thick.

Precautions

- Do Not Heat or Thin
- Do Not Store Container at Temperatures Above 100 °F
- Combustible. Contains Petroleum Distillate

Safety & Environmental Precautions

- Refer to Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container when Not in Use
- Environmental Information is on The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) is 300 Gm/Liter Max
- Use with Adequate Ventilation
- Keep Out of Reach Of Children

This product does not contain any California Proposition 65 Chemicals.

Premium All-Weather Roof Patch & Flashing Cement
 Professional Quality Water Repellent Sealing Compound

Form No.: JC-TD61415

Packaging

Item #	Container Size	Pack	Weight
61415	4.75 Gallon Pail	1	50 lbs.
61411	.9 Gallon Pail	6	56 lbs.
61429	10 Oz. Tube	12	11 lbs.

* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Asphalt	8052-42-4
Mineral Spirits	64742-88-7
Amine Salt	28701-67-9
Cellulose	9004-34-6
Attapulgite Clay	12174-11-7