



Resin Treated Multi-Purpose Reinforcing Fabric

Superior Reinforcing Material

- Reinforces & Strengthens Patchwork for Lasting Repairs
- Resin Coated for Superior Cohesion with Patching Materials
- Use with Asphalt & Elastomeric Cements
- Meets ASTM D-1668 Type III



Manufacturer:

JETCOAT
 472 Brehl Avenue
 Columbus, Ohio
 Phone: 800-394-0047
 Fax: 614-279-7201
 www.JETCOATinc.com

Description

Ideal for use with asphalt & elastomeric roof cements to strengthen repairs on cracks, gutters, flashings, seams and more.

Uses

- Cracks
- Gutters
- Blisters
- Seams
- Flashing

Surface Preparation

For best results, clean area of loose dirt and debris. If moisture is present allow area to dry.

Application

CRACKS, BREAKS, LOOSE SEAMS: Clean area of loose dirt and debris. If moisture is present allow area to dry. Apply roof cement to defective area. Extend coating to three inches beyond area to be repaired. Spot stick reinforcing fabric in position over defect. Press into place. Top coat with roofing cement.

FLASHINGS: Spread roof cement into cracks extending 3" to each side of crack. Firmly press reinforcing fabric into coating and top coat with more roof cement.

GUTTERS: Clean gutter of dirt and rust. Dry area to be patched if wet. Place heavy coating of roof cement over defective area. Firmly press reinforcing fabric into coating and top coat with more roof cement.

BLISTERS: Leaking blisters should be slit in a criss-cross pattern and folded open. Damaged materials should be removed. Allow area to dry if wet. Apply roof cement to opened area with putty knife or trowel. Replace criss-cross cut material to close opening. Press into place. Cover area with roof cement. Extend coating 3" beyond defective area. Firmly press reinforcing fabric into coating and top coat with more roof cement.

Coverage (Approximate)

- 6 inches wide X 50 feet long.

Safety And Environmental Precautions

- Refer to Material Safety Data Sheet before using.
- FOR EXTERIOR APPLICATION ONLY.
- Environmental information is on the Material Safety Data Sheet.
- KEEP OUT OF REACH OF CHILDREN.

This product does not contain any California Proposition 65 Chemicals.

Packaging

| Item # | Container Size | Pack | Weight |
|--------|----------------|------|----------|
| 61762S | 6" X 50' Roll | 12 | 6.5 lbs. |

Resin Treated Multi-Purpose Reinforcing Fabric
 Superior Reinforcing Material

Form No.: JC-TD61762S

