

# ACRYLIC CRACK FILLER

## Fills and seals cracks in asphalt and concrete sport surfaces

- 100% acrylic
- Highly Durable
- Can be used on asphalt or concrete surfaces

### MANUFACTURER

JETCOAT  
472 Brehl Avenue  
Columbus, Ohio 43223  
Phone: 800-394-0047  
Fax: 614-279-7201  
www.JETCOATinc.com

### DESCRIPTION

Surface 1 Crack Filler is a 100% acrylic crack filler for filling cracks in asphalt or concrete sport surfaces up to 1" in width. Surface 1 Crack Filler can also be used for minor depressions and surface imperfections.

### USES

Asphalt or concrete sport surfaces, play areas, and all-purpose recreational surfaces.

### COLORS

Acrylic Crack Filler is available in green, red and neutral colors. Neutral can be tinted with pigment to add color. Acrylic Crack Filler can be coated over, but it is not necessary.

### SURFACE PREPARATION

Surface must be clean and free from loose materials such as dirt, debris and vegetation. Clean cracks with pressure washer or air compressor. Avoid application during periods of excessive moisture in cracks or beneath pavement surface.

Allow crack filler to dry prior to applying Surface 1 One Coat Color (dry time varies depending on width and depth of crack).

### APPLICATION

Stir pail thoroughly. Surface 1 Acrylic Crack Filler is ready-to-use. Do not dilute. Apply Surface 1 Crack Filler into crack with a trowel or putty knife, making sure to scrape off excess material with application tool. A damp cloth or sponge can be used to ensure a smooth finish during application.

### CLEAN UP

Wash tools with water before material dries.

### WEATHER CONDITIONS

Application temperature must be a minimum of 50 °F and rising. Do not apply when temperature is expected to drop below 50 °F within a 24- hour period.

In areas where dew or fog accumulates in the early evening, it is best to coat in the morning.

Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrives before crack filler dries.

Do not apply if rain is imminent or forecast within 24 hours of application.

### COVERAGE (APPROXIMATE)

1 gallon will fill approximately 75 to 150 lineal feet, depending on the width and depth of the cracks.

### PRECAUTIONS

Do Not Freeze. Do Not Store At Temperatures Below 50 °F.

### CAUTION

KEEP OUT OF REACH OF CHILDREN. Protect from freezing. Do not take internally. If swallowed, call a physician immediately. In case of contact with eyes, flush immediately with water for 15 minutes and call a physician. Store material with container tightly closed and upright to avoid spillage. Do not store

material in direct sunlight or in areas exceeding 100 degrees Fahrenheit. In case of spill, absorb and dispose of in accordance with Federal, State, and local regulations.

**LIMITED WARRANTY**

JETCOAT warrants this product to be of merchantable quality, when used or applied in accordance with the instructions hereon. JETCOAT does not warrant this product to be suitable for any particular use or purpose other than for which it is intended. Liability is limited to replacement of the product, or at its option, to a refund of the price thereof. There are no other warranties either expressed or implied. Liability for any incidental or consequential damage or loss is specifically excluded at all times.