

LINE PRIMER

Acrylic Coating

- 100% acrylic
- Dries clear

MANUFACTURER

JETCOAT
472 Brehl Avenue
Columbus, Ohio 43223
Phone: 800-394-0047
Fax: 614-279-7201
www.JETCOATinc.com

DESCRIPTION

Surface 1 Line Primer is a 100% acrylic, clear drying primer that is applied between the masking tape and court surface. Application of Surface 1 Line Primer will prevent line paint from bleeding under the tape to achieve sharp lines.

USES

For priming line markings on any asphalt, concrete or color coated surface.

SURFACE PREPARATION

Surface must be clean and free from loose materials such as dust, dirt and debris.

APPLICATION

Shake jug thoroughly. Surface 1 Line Primer is ready-to-use. Do not dilute. Surface 1 Line Primer can be applied by brush or roller. Apply between two rows of masking tape, prior to Surface 1 White Line Paint, making sure to overlap onto the inside edge of tape on each side. This will enable the Surface 1 Line Primer to bleed under the tape and seal off minor surface voids. Allow Surface 1 Line Primer to dry completely before applying Surface 1 White Line Paint.

DRYING TIME

Drying time is dependent on temperature, shade,

humidity, etc. (1 to 4 hours of dry time per coat can be expected).

CLEAN UP

Wash tools with water before material dries.

WEATHER CONDITIONS

Application temperature must be a minimum of 50 °F and rising. Do not apply when temperature is expected to drop below 50 °F within a 24- hour period.

In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrives before coating dries.

Do not apply if rain is imminent or forecast within 24 hours of application.

COVERAGE (APPROXIMATE)

1 gallon will cover 500 to 600 lineal feet of 2 inch line.

PRECAUTIONS

Do Not Freeze. Do Not Store At Temperatures Below 50 °F.

CAUTION

KEEP OUT OF REACH OF CHILDREN. Protect from freezing. Do not take internally. If swallowed, call a physician immediately. In case of contact with eyes, flush immediately with water for 15 minutes and call a physician. Store material with container tightly closed and upright to avoid spillage. Do not store material in direct sunlight or in areas exceeding 100 degrees Fahrenheit. In case of spill, absorb and dispose of in accordance with Federal, State, and local regulations.



LIMITED WARRANTY

JETCOAT warrants this product to be of merchantable quality, when used or applied in accordance with the instructions hereon. JETCOAT does not warrant this product to be suitable for any particular use or purpose other than for which it is intended. Liability is limited to replacement of the product, or at its option, to a refund of the price thereof. There are no other warranties either expressed or implied. Liability for any incidental or consequential damage or loss is specifically excluded at all times.